


imageRUNNER C1225iF

Productive and cost effective A4 colour multifunctional

The imageRUNNER C1225iF is a feature rich A4 colour multifunctional device, providing fast and efficient document handling 'out of the box' so you can focus on your business priorities.



- Powerful A4 colour multifunctional with print, copy, colour scan, send and fax functionality, ideal for demanding small businesses
- Simple and user friendly operation with the 8.9 cm colour touch and swipe LCD display
- Canon's V² colour (Vivid and Vibrant) imaging technology ensures documents impress and stand out from the rest
- Seamlessly fits into your office environment with network connectivity and supporting IT standards such as PCL and Genuine Adobe PS
- Increase productivity with up to 1,100 sheet capacity and a Duplex Automatic Document Feeder (DADF)
- Scan and Send documents directly to a variety of destinations including email and shared folder
- Flexible mobile printing and scanning capabilities such as Apple AirPrint™, Mopria printing as well as mobile printing and scanning apps, support mobile worker efficiency
- Out of the box easy install; users can access the set-up guide via the user interface
- Consumables can be changed easily reducing down-time
- Standard toner included in the box giving up to 12 months colour printing¹
- Giving you peace of mind with Canon's standard warranty
- Energy consumption as little as 1 watt in sleep mode
- Compact and efficient space saving design



PRINT



COPY



FAX



SCAN

AirPrint™ and the AirPrint logo are trademarks of Apple Inc.
¹Actual results will vary and may be higher or lower than 12 months depending on individual usage. 12 months colour printing is based on a monthly print volume of 1,000 pages, 30% colour pages and 5% A4 coverage (ISO/IEC 24712). Standard Black toner yield is 12,000 pages. Yellow, Magenta and Cyan toner yield is 7,300 pages

Technical Specifications

imageRUNNER C1225iF

<p>Machine type</p> <p>Available core functions</p> <p>Printer Specifications</p> <p>Print speed (BW/Colour)</p> <p>Printing method</p> <p>Print resolution</p> <p>Double sided printing</p> <p>Direct print</p> <p>Printing from mobiles or internet-connected devices and cloud-based services</p> <p>Paper input (Standard)</p> <p>Paper input (Option)</p> <p>Maximum paper input capacity</p> <p>Paper output capacity</p> <p>Finishing capabilities</p> <p>Supported media types</p> <p>Supported media sizes</p> <p>Supported media weights</p> <p>Page Description Language(s)</p> <p>Fonts</p> <p>Operating System compatibility</p> <p>Copy Specifications</p> <p>Copy speed (BW/Colour)</p> <p>First Copy Output Time (FCOT) (BW/Colour)</p> <p>Copy resolution</p> <p>Multiple copy Reduction/Enlargement</p> <p>Scan Specifications</p> <p>Optional/Standard</p> <p>Supported media size/s</p> <p>Supported media weight/s</p>	<p>Colour A4 Laser Multifunctional (Reader / Printer standard)</p> <p>Print, Copy, Scan, Send and Fax standard for C1225iF</p> <p>25/25ppm (A4 Single-sided), 26/26ppm (A5 Single-sided), 25/25ppm (A4 Double-sided), 26/26ppm (A5 Double-sided)</p> <p>Colour Laser Beam Printing</p> <p>2400 dpi equivalent x 600 dpi, 600 dpi x 600 dpi</p> <p>Automatic (Standard)</p> <p>Direct printing available from USB memory key Supported file types: JPEG, TIFF, PDF</p> <p>A range of software is available to provide printing from mobile or internet-connected devices. Please contact your sales representative for further information.</p> <p>1 x 550-sheet (80 gsm) cassette, 100-sheet (80 gsm) multi-purpose tray</p> <p>1 x 550-sheet cassette (80 gsm) (Cassette Feeding Unit-AJ1)</p> <p>1200 sheets (80 gsm)</p> <p>250 sheets (80 gsm)</p> <p>Standard: Collate, Group</p> <p>Cassette/s: Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Envelopes* *Envelope support via standard cassette 1 only.</p> <p>Multi-purpose tray: Thin paper, Plain paper, Recycled paper, Colour paper, Heavy paper, Pre-punched paper, Transparency, Labels, Envelopes (No.10 (COM10), Monarch, ISO-C5, DL)</p> <p>Paper cassette 1: Standard size: A4, A5, B5, Legal, Letter, Executive, Statement, Envelopes (No.10 (COM10), Monarch, DL) Custom size (98.4 mm to 216 mm X 190.5 mm to 355.6 mm)</p> <p>Paper cassettes 2: Standard size: A4, A5, B5, Legal, Letter, Executive, Statement Custom size (98.4 mm to 216 mm X 190.5 mm to 355.6 mm)</p> <p>Multi-purpose tray: Standard size: A4, A5, B5, Legal, Letter, Executive, Statement, Custom size (98.4 mm to 216 mm x 148 mm to 355.6 mm), Envelopes (No.10 (COM10), Monarch, ISO-C5,DL)</p> <p>Cassette/s : 60 to 163 gsm Multi-purpose tray: 60 to 220 gsm Duplex: 60 to 163 gsm</p> <p>UFRII , PCL5c/6, Adobe PostScript Level 3 (Standard for C1225iF)</p> <p>PCL fonts: 93 Roman, 10 Bitmap, 2 OCR fonts PS fonts: 136 Roman fonts</p> <p>UFRII: Windows XP / Server 2003 / Vista / Server 2008 / Windows 7 / Server 2008R2 / Windows 8 / Windows 8.1 / Server 2012 / Server 2012R2, MAC OS X (10.5.8 or later)</p> <p>PCL: Windows XP / Server 2003 / Vista / Server 2008 / Windows 7 / Server 2008 R2 / Windows 8 / Windows 8.1 / Server 2012 / Server 2012R2</p> <p>PS: Windows XP / Server 2003 / Vista / Server 2008 / Windows 7 / Server 2008 R2 / Windows 8 / Windows 8.1 / Server 2012 / Server 2012R2, MAC OS X (10.5.8 or later)</p> <p>PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or later), Windows XP / Windows Vista / Windows 7 / Windows 8 / Windows 8.1</p> <p>Please refer to http://software.canon-europe.com/ for availability of print solutions for other operating systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place.</p> <p>Please refer to the quoted print speeds</p> <p>8.4 sec / 10.5 sec</p> <p>Reading: 600 dpi x 600 dpi Printing: 600 dpi x 600 dpi</p> <p>Up to 999 copies Zoom: 25 - 400 % in 1 % increments Fixed Zoom Ratio: 25%, 50%, 70%, 100%, 141%, 200%, 400%</p> <p>Standard on all models (DADF 50 sheets)</p> <p>A4, A5, B5, Custom sizes: 140 mm to 216 mm x 128 mm to 356 mm (when fed through the DADF)</p> <p>Single-sided scanning: 50 to 105 gsm (DADF) Double-sided scanning: 64 to 105 gsm (DADF)</p>	<p>Scan resolution</p> <p>Double sided scanning</p> <p>Scan speed</p> <p>Scan methods</p> <p>Pull scan specifications</p> <p>Send Specifications</p> <p>Optional/Standard</p> <p>Send resolution</p> <p>Destinations</p> <p>Address Book/Speed dials</p> <p>File formats</p> <p>Optional Universal Send Feature Sets</p> <p>Fax Specifications</p> <p>Optional/Standard</p> <p>Modem speed</p> <p>Fax resolution</p> <p>Fax memory</p> <p>Speed dials</p> <p>Group dials / destinations</p> <p>Sequential broadcast</p> <p>Memory backup</p> <p>Other features</p> <p>General Specifications</p> <p>Warm-up time</p> <p>Recovery from sleep mode</p> <p>Interface type</p> <p>Network protocols</p> <p>Memory</p> <p>Control panel</p> <p>Dimensions (W x D x H)</p> <p>Installation space (W x D)</p> <p>Weight</p> <p>Operating environment</p> <p>Power source</p> <p>Power consumption</p>	<p>BW Scan: 100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi, 200 dpi x 400 dpi, 400 dpi, 600 dpi</p> <p>CL Scan: 100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi</p> <p>2-sided to 2-sided (Automatic)</p> <p>BW single-sided: 25 ipm (A4, 300 dpi X 300 dpi), BW double-sided: 9 ipm (A4, 300 dpi X 300 dpi) CL single-sided: 25 ipm (A4, 300 dpi X 300 dpi), CL double-sided: 9 ipm (A4, 300 dpi X 300 dpi)</p> <p>Push Scan: Colour Send functionality is standard. Pull Scan: TWAIN/WIA Pull scanning available on all models. Scan to USB Memory Key: Available on all models Scan to mobiles, internet-connected devices: A range of solutions is available to provide scanning to mobile devices, internet-connected devices depending on your requirements. Please contact your sales representative for further information.</p> <p>TWAIN/WIA Pull scanning Windows XP Windows Vista/Windows 7/Windows 8/Windows 8.1</p> <p>Mac Scan (TWAIN only) Mac OS X 10.5.8 or later</p> <p>*The drivers are available via http://software.canon-europe.com.</p> <p>Standard on all models</p> <p>100 dpi, 150 dpi, 200 dpi x 100 dpi, 200 dpi, 300 dpi, 200 dpi x 400 dpi, 400 dpi, 600 dpi</p> <p>E-Mail, Fax (not available for C1225), PC (SMB, FTP) LDAP (Max. 50 searchable), Local (Max. 300 including 281 Speed dials)</p> <p>SMB : JPEG, TIFF, PDF, Compact PDF, Searchable PDF E-mail : PDF, Compact PDF, Searchable PDF</p> <p>Send PDF Security Feature Set-E1@E: Send encrypted PDF and add digital device signature to PDF files.</p> <p>Standard for C1225iF</p> <p>Super G3 33.6 kbps (Up to 3 seconds per page)</p> <p>Standard: 200 x 100 dpi Fine: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi</p> <p>Up to 512 pages¹ Max. 281</p> <p>Max. 199 dials</p> <p>Max. 310 addresses</p> <p>Yes</p> <p>Fax Forwarding, Dual Access, PC Fax (TX only)</p> <p>Approx. 34 seconds from power ON</p> <p>10 seconds or less</p> <p>USB 2.0 Hi-Speed, 1000BaseT / 100Base-TX / 10Base-T, 1 x USB Host (Front), 1 x USB Host (Rear), 1 x USB device Recommended third party wireless solution is Silix SX-BR-4600 WAN. For more details please refer to www.silix-europe.com</p> <p>TCP/IP* (LPD / Port 9100 / WSD / IPP / IPPS / SMB / FTP), IPX/SPX (NDS, Bindery) *IPv4/IPv6 support</p> <p>1.0 GB</p> <p>QVGA Color LCD 8.9 cm (3.5 inch) touch / swipe supported display</p> <p>Standard: 511 mm x 549 mm x 610 mm</p> <p>Optional: With Cassette Feeding Unit-AJ1: 511 mm x 549 mm x 1035 mm</p> <p>852 mm x 843 mm (Main unit + Multi-purpose tray open + Cassette drawers open)</p> <p>Approx. 44 kg including toner</p> <p>Temperature: 10 to 30°C (50 to 86°F) Humidity: 20 to 80 % RH (no condensation)</p> <p>220 - 240 V (±10 %), 50/60 Hz (±2 Hz), 3.7 Amp</p> <p>Maximum: Approx. 1.5 kW Standby: Approx. 30 W Sleep mode: Approx. 1.0 W or less² Time to put the device to sleep mode : 60 sec Typical Electricity Consumption (TEC) rating³: 0.8 kWh</p> <p>Only for C1225 (non Fax model) Plugin-off: 0.5W or less (Normal mode) Time to put the device to plugin-off: 4 hours</p>
--	--	---	--

Technical Specifications

imageRUNNER C1225iF

Noise levels
Sound Pressure ⁴
(reference data, LpAm,
Bystander's position)
Software and printer
management

Sound Pressure Noise Levels:
 Active: 50 dB
 Standby: Inaudible (Less than 30dB)

eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics.

Remote Firmware System (GDLS):

Allows the remote distribution of firmware.

Remote User Interface (RUI): Web-based interface to each device that helps to provide remote device management and control.

Canon Driver Configuration Tool: A utility for changing the factory default settings of Canon print drivers

Standard:
 IP/Mac Address Filtering, IPSEC, SNMP V3.0, IEEE 802.1X, Secured Print, Department ID
 Optional: Send PDF Security Feature Set-E1@E

Toner 34 Black / Cyan / Magenta / Yellow Toner
 (Yield: BK 12,000 / CMY 7,300 pages)⁵

Security features

Consumables

Toner bottle

Specifications for options

Cassette feeding unit

Name: Cassette Feeding Unit-AJ1
 Description: Optional cassette feeding unit with 1 x 550 sheets paper capacity. Takes the cassette paper capacity up to 1,200 sheets.
 Dimensions (W x D x H): 511 mm x 508 mm x 425 mm
 Weight: Approx. 15 kg

HANDSET-J1 EUR/HANDSET-J1 SA

BARCODE PRINTING KIT-D1@E: Enables barcode printing via jet caps technology.

Send PDF Security Feature Set-E1@E: Send encrypted PDF and add digital device signature to PDF files.

Drum Unit 034 (BK / C / M / Y)

Waste Toner Box WT-A3:

Hardware accessories 1

Print controller accessories

Document security accessories

Other options

Footnotes

¹Based on ITU-T Standard Chart No. 1

²1 watt sleep mode may not be possible in all circumstances. Certain network configurations and options may prevent the device from entering deep sleep mode. Please refer to the user guide for more information

³Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh). The test methodology is defined by Energy Star (<http://www.eu-energystar.org>).

⁴Declared noise emission in accordance with ISO 7779

⁵Based on 5% coverage (A4)

All specifications subject to change without notice



Canon Inc.
 canon.com

Canon Europe
 canon-europe.com

UK English edition
 © Canon Europa N.V., 2015

Canon (UK) Ltd
 Woodhatch
 Reigate
 Surrey RH2 8BF
 Telephone no 01737 220000
 Facsimile 01737 220022
 canon.co.uk

Canon Ireland
 3006 Lake Drive
 Citywest, Saggart
 Co.Dublin, Ireland
 Telephone No: 01 2052400
 Facsimile No: 01 2052525
 canon.ie

